

Instance Manager: Ready to acquire

Instance	Status	LEs: 52175	Memory: 4692	Small: 7345/91	Medium: 0/12	Large: 0/22
sgdma_input_output	Not running	3919 cells	316416 bits	0 blocks	0 blocks	0 blocks
Decoder_output	Not running	3598 cells	287744 bits	0 blocks	0 blocks	0 blocks
IsLimitUpdate_output	Not running	3311 cells	520192 bits	0 blocks	0 blocks	0 blocks
Demux_output	Not running	4986 cells	819200 bits	0 blocks	0 blocks	0 blocks
OFI_3	Not running	4103 cells	332800 bits	0 blocks	0 blocks	0 blocks
OFI_2	Not running	2898 cells	225280 bits	0 blocks	0 blocks	0 blocks
OFI_1	Not running	8886 cells	380928 bits	0 blocks	0 blocks	0 blocks
price_converter	Not running	2853 cells	221184 bits	0 blocks	0 blocks	0 blocks
mux	Not running	1637 cells	112640 bits	0 blocks	0 blocks	0 blocks
Packet_choper	Not running	7223 cells	611328 bits	0 blocks	0 blocks	0 blocks
MDIO	Not running	478 cells	20480 bits	0 blocks	0 blocks	0 blocks
OFI_4	Not running	2772 cells	108032 bits	0 blocks	0 blocks	0 blocks

JTAG Chain Configuration: JTAG ready

Hardware: USB-Blaster [USB 3-1] Setup...

Device: @1: EP4SGX230(.JES) (0x024C) Scan Chain

SOF Manager: _design_hardware.sof

Attached SOF: pcie_core_rst_ compatible, pcie_core_ctrl_ compatible, pcie_core_out_ compatible

